



Description

Exocet Anti-Wax is formulated to improve the cold flow and handling properties of diesel and gas oil.

Application

Exocet Anti-Wax is typically added at the rate of 1 litre of additive to 1,000 litres of fuel. The additive must be used as preventative measure and will not work if the fuel is already waxed. Fuel-specific tests need to be carried out if a minimum operability temperature is required.

Features

- Boosts the fuel's resistance to waxing
- Allows operation at colder temperatures than fuel specification
- Inhibits the formation of wax crystals
- Reduces the potential for filter plugging
- Works with maximum allowable FAME contents

All exocet™ branded products are available in a range of sizes to 1,000 litres

Example Performances

	EN590 Diesel Summer	EN590 Diesel Winter	Class A2 Gas Oil Summer	Class A2 Gas Oil Winter
CFPP Specification	-5°C	-15°C	-4°C	-12°C
CFPP With Exocet additive	-18°C	-26°C	-19°C	-28°C
Treat rate Additive:Fuel	1:1000	1:1000	1:1000	1:1000



T : +44 (0)1743 761415
F : +44 (0)1743 761075
E : sales@fastexocet.co.uk

Fuel Additive Science Technologies Ltd
 Unit 29 Atcham Business Park, Upton Magna,
 Shrewsbury, Shropshire, SY4 4UG

T : +353 (0)1 808 4805
F : +353 (0)1 808 4789

Fuel Additive Science Technologies Ltd
 Block A, Unit 7, Airside Enterprise Centre, Swords,
 Co. Dublin.